

INDUSTRIAL COMPONENT DATA

FCFSDNH00BB100 149430 Y7-149430 EATON ELECTRIC
FCFSDNH00BB100

Brand: EATON - MOELLER | Manufacturer Part Number: FCFSDNH00BB100



Manufacturer	EATON - MOELLER
MPN / Reference	FCFSDNH00BB100
Catalog number	Y7-149430
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-22B282177E
Generated	2026-08-05

Product Overview

FCFSDNH00BB100

Low-voltage h.b.c fuse switch strip, 160A, size 00

Interval between phase centers 100mm size 00

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

Low-voltage h.b.c fuse switch strip, 160A, size 00Interval between phase centers 100mm size 00Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)Electric engineering, automation,
process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch
disconnecter ( [AKF058013])Version as main switchNoVersion as safety switchNoMax. rated operation
voltage Ue AC690 VRated permanent current Iu160 ARated operation power at AC-23, 400 V372 kWConditioned rated
short-circuit current Iq80 kARated short-time withstand current Icw0 kASuitable for fusesNH00Number of poles3With error
protectionNoType of electrical connection of main circuitBolt connectionCable entryOtherEquipped with
connectorsNoSuitable for ground mountingNoSuitable for front mounting 4-holeNoSuitable for busbar mountingYesType of
control elementRocker leverPosition control elementFront sideMotor drive optionalYesMotor drive integratedNoVersion as
emergency stop installationNoDegree of protection (IP), front sideIP30
ETIM for 149430 Low-voltage industrial controls and switchgear (EC001040)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as safety switch (EF006985)

No

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

160 A

Rated operation power at AC-23, 400 V (EF007027)

0 kW

Conditioned rated short-circuit current Iq (EF001444)

80 kA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FCFSDNH00BB100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.