

INDUSTRIAL COMPONENT DATA

PKNM-10/1N/C/01-A-MW 236083 EATON ELECTRIC RCD/MCB combination switch, 10A, 100mA, C-LS-Char, 1N pole, FI-Ch..

Brand: EATON - MOELLER | Manufacturer Part Number: PKNM-10/1N/C/01-A-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PKNM-10/1N/C/01-A-MW
Catalog number	236083
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-FDDABBF370
Generated	2026-08-05

Product Overview

RCD/MCB combination switch, 10A, 100mA, C-LS-Char, 1N pole, FI-Char: A

High-quality residual current circuit-breaker/miniature circuit-breaker combination independent of grid voltage, contact position display red-green, terminal rear plug protection, tri-stable slide catch-enables removal from an existing closure assembly, comprehensive accessory product range can be retrofitted, wide range of rated fault currents, rated operational currents up to 40 A, trip types B, C, rated switching capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - PKN6/M RCBO - residual-current circuit breaker with overcurrent protection

Catalog Number 236083 Model Code PKNM-10/1N/C/01-A-MW EAN 4015082360832 Product Length/Depth 80 mm

Product Height 75 mm Product Width 35 mm Product Weight 0.189 kg Compliances CE Marked

RoHS conform Delivery program

Application Switchgear for residential and commercial applications Basic function Combined RCD/MCB devices Number of poles Single-pole + N Number of poles (protected) 1 Number of poles (total) 2 Release characteristic C Rated current 10 A Fault current rating 0.1 A Type RCBO Technical data - electrical

Voltage type AC Voltage rating 230 V Frequency rating 50 Hz Leakage current type A Rated short-circuit breaking capacity (EN 60947-2) 0 kA Surge current capacity 0.25 kA Overvoltage category III Pollution degree 2 Technical data - mechanical

Width in number of modular spacings 2 Built-in depth 70 mm Degree of protection IP20 Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In) 10 A Heat dissipation per pole, current-dependent 0 W Equipment heat dissipation, current-dependent 2.5 W Static heat dissipation, non-current-dependent 0 W Heat dissipation capacity 0 W Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requireme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKNM-10/1N/C/01-A-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.