

INDUSTRIAL COMPONENT DATA

FIPA-XAM011 262578 Y7-262578 EATON ELECTRIC Auxiliary contact, for FI..., 1W+1N/C, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: FIPA-XAM011



Manufacturer	EATON - MOELLER
MPN / Reference	FIPA-XAM011
Catalog number	Y7-262578
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-F0FACAC64E
Generated	2026-08-02

Product Overview

Auxiliary contact, for FI..., 1W+1N/C, 0.5HP

FIPA-XAM011

FI..., for 1W+1N/C, 0.5auxiliary contacts, for FI..., 1W+1N/C, 0.5 SU auxiliary contact, 1W+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Auxiliary contact, for FI..., 1W+1N/C, 0.5HPFI..., for 1W+1N/C, 0.5auxiliary contacts, for FI..., 1W+1N/C, 0.5 SU auxiliary contact, 1W+1N/CSU

General specificationsProduct nameEaton Distribution partsPart no.FIPA-XAM011EAN4015082625788Product

Length/Depth62 millimetreProduct height75 millimetreProduct width9 millimetreProduct weight0.06

kilogramCompliancesRoHS conformCertificationsEN45545-2

IEC 61373Product TradenameNoneProduct TypeDistribution partsProduct Sub TypeNonePublic ConsumptionYesProduct

Family DescriptionES-PMCC-PDC-Eaton Distribution partsGlobally MarketableYesProduct Specification

DetailsAccessory/spare part typeAuxiliary contactsAdditional equipment requiredOtherAdmissible back-up fuse - max6 A

gLAmbient operating temperature - max40 °CAmbient operating temperature - min-5 °CAssembly width0.5Contact

function1 C/O + 1 BDegree of protectionIP40Device fittingUniversalEnclosure width90 mmFrameStandard front dimension:

45 mmFrequency rating50 Hz / 60 HzFunctionsAuxiliary switchMounting width8.8 mm (0.5 space units)Number of contacts

(change-over contacts)1Number of contacts (normally closed contacts)1Number of contacts (normally open

contacts)0Number of poles at main contact unit - max2Number of switches (fault signal)0Rated insulation voltage (Ui)440 V

ACRated operational current1 A (230 V DC-11)

6 A (230 V AC-11)Rated operational voltage (Ue) - max230 VRated switch current3 ASpecial featuresIP20 (switch)Suitable for current of main contact unit - max0 ATerminal capacit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FIPA-XAM011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.