

INDUSTRIAL COMPONENT DATA

**SOL30-SAFETY/2MV-U(230V50HZ) 144123 Y7-144123 EATON
ELECTRIC Fireman's switch, 30A, MV, UA 230V50Hz**

Brand: EATON - MOELLER | Manufacturer Part Number: SOL30-SAFETY/2MV-U(230V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SOL30-SAFETY/2MV-U(230V50HZ)
Catalog number	Y7-144123
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-19A67E466B
Generated	2026-08-06

Product Overview

Fireman's switch, 30A, MV, UA 230V50Hz

SOL30-SAFETY/2MV-U(230V50HZ)

Eaton Moeller® series SOL30 Safety Fireman's switch, 25A, MV, UA 230V50Hz

Fireman's switch, Degree of Protection: IP65, Standards: IEC/EN 60 947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Solar Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series SOL30 Safety Fireman's switch Catalog Number 144123 Model Code SOL30-SAFETY/2MV-U(230V50HZ) EAN 4015081406333 Product Length/Depth 224 mm Product Height 130 mm Product Width 100 mm Product Weight 1.006 kg Certifications IEC/EN 60 947-3 Features & Functions Actuator color Black Actuator type Toggle Features Version as maintenance-/service switch Fitted with: Voltage release optional Locking facility Lockable in the 0 (Off) position (with padlock) Number of poles Two-pole General Application Connection type M12, Outputs M12, Inputs Degree of protection NEMA Other Degree of protection (front side) IP65 Lifespan, electrical 1,500 Operations Lifespan, mechanical 100,000 Operations Operating frequency 120 Operations/h Overvoltage category III Pollution degree 3 Product Category Fireman's Switch Switchgear for photovoltaic systems Rated impulse withstand voltage (Uimp) 8000 V Suitable for Ground mounting Utilization category DC-21 A Climatic

environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Contacts

Number of auxiliary contacts (change-over contacts) 1 Number of auxiliary contacts (normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 0 Electrical rating

Rated operational current (Ie) at DC-21A 30 A Rated operational power at AC-23A, 400 V, 50 Hz...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SOL30-SAFETY/2MV-U(230V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.