

INDUSTRIAL COMPONENT DATA

RA-C1-PLF 290188 Y7-290188 EATON ELECTRIC Rapid Link 4 Flat Cable Connector 400V / 24V

Brand: EATON - MOELLER | Manufacturer Part Number: RA-C1-PLF



Manufacturer	EATON - MOELLER
MPN / Reference	RA-C1-PLF
Catalog number	Y7-290188
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-5FCAF7D95E
Generated	2026-08-02

Product Overview

Rapid Link 4 - Flat Cable Connector 400V / 24V

RA-C1-PLF

Flat cable outgoer, for 400VAC, +24VDC

Flexible busbar junction for 400 V and 24 V DC with terminal socket and locking clips, cable termination with insulation displacement tool-less

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Rapid Link Starters

Additional Product Information

Flat cable outgoer, for 400VAC, +24VDCFlexible busbar junction for 400 V and 24 V DC with terminal socket and locking clips, cable termination with insulation displacement tool-less

General specificationsProduct nameEaton Moeller® series Rapid Link Accessory Flexible busbar junctionPart no.RA-C1-PLFEAN4015082901882Product Length/Depth119 millimetreProduct height53 millimetreProduct width57.5 millimetreProduct weight0.134 kilogramCertificationsEN 60998-2-3

IEC/EN 60529Product TradenameRapid LinkProduct TypeAccessoryProduct Sub TypeFlexible busbar junctionCatalog NotesInsulation piercing terminals, terminal socket with lock mechanismGeneral informationAccessory/spare part typeConnection techniqueDegree of protectionIP65, according to IEC/EN 60529Product categoryAccessoriesTypeConnection socket (for power connection cable)Ambient conditions, mechanicalMounting positionAs requiredClimatic environmental conditionsAmbient operating temperature - min-30 °CAmbient operating temperature - max55 °CAmbient storage temperature - min-40 °CAmbient storage temperature - max70 °CMain

circuitRated operational current (Ie)20 ARated operational voltage (Ue) at AC - max500 VRated operational voltage (Ue) at DC - max24 VContactsContact typeIDC terminationDesign verification10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RA-C1-PLF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.