

INDUSTRIAL COMPONENT DATA

BP-F-1200/20/3-F-IVS-W 111410 EATON ELECTRIC Floor standing distribution board

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1200/20/3-F-IVS-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1200/20/3-F-IVS-W
Catalog number	111410
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-6C34A0A776
Generated	2026-08-05

Product Overview

Floor standing distribution board

Service distribution boards IVS are used for power distribution and measurement purposes in electrical systems for household electrical systems and in comparative systems such as residential buildings, schools, administration centers, offices and similar buildings.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Product range Service distribution board IVS

Basic function Floor-standing enclosures

Single unit/Complete unit Complete housing

Degree of Protection IP30 (only with door)

Description Profi Plus basic enclosures without door

Exchangeable door hinges

Material Sheet steel

Surface finish Polyester powder coating

Phosphated

RAL 9016, traffic white

Colour RAL 9016, traffic white

Information about equipment supplied Including mounting system for the IVS mounting units

including insulating surround and mounted insulated support bracket

including cable entry top and bottom, with push-through flange

Width mm 1200

Height mm 2060

Depth mm 300

Technical data General

Standards EN 60439-1/3

IEC 62208

Protection class 1

Degree of Protection IP30 (only with door)

Power loss

Max. admissible heat dissipation, ambient air temperature +35 °C W 519

Weight kg 69.5

Material characteristics

Material Sheet steel

Surface treatment Painting, phosphated and polyester powder coating

Surface finish Polyester powder coating

Phosphated

RAL 9016, traffic white

Colour RAL 9016, traffic white

Material characteristics

Type Door Doors with covered hinges

Can be removed from 90°

door opening angle 167° (single mounting)

60° (combination mounting)

Door interlock Hinge handle with three-point turn-lock

Cylinder lock

Material properties

Mechanical

Impact resistance IK07

Cable entry Various covers allow cable entry from above and/or below

Electrical

Rated operational voltage Ue V 690

Rated frequen...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1200/20/3-F-IVS-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.