

INDUSTRIAL COMPONENT DATA

BPM-F-1350/19/2-P-EP 147413 EATON ELECTRIC
Floor-standing distribution board, EP, IP55, HxWxD
1910x1350x250mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-1350/19/2-P-EP



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-1350/19/2-P-EP
Catalog number	147413
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-E10A78A05A
Generated	2026-08-04

Product Overview

Floor-standing distribution board, EP, IP55, HxWxD=1910x1350x250mm

The standard flush-mounting EP system is a system for surface mounting factory finished, type-tested switchgear assemblies

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor-standing distribution board, EP, IP55, HxWxD=1910x1350x250mm The standard flush-mounting EP system is a system for surface mounting factory finished, type-tested switchgear assemblies [Design verification as per IEC/EN 61439 Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure, free-standing [PV] 280 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure, free-standing [PV] 279 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure, free-standing [PV] 278 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV] 254 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV] 250 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure for wall mounting [PV] 248 W Heat

dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 561 W Heat dissipation, at an amb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-1350/19/2-P-EP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.