

INDUSTRIAL COMPONENT DATA

BPM-F-600/20/2-P-EP 142445 EATON ELECTRIC
Floor-standing distribution board, EP, IP55, HxWxD
2060x600x250mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-600/20/2-P-EP



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-600/20/2-P-EP
Catalog number	142445
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-3F29DAFEB9
Generated	2026-08-05

Product Overview

Floor-standing distribution board, EP, IP55, HxWxD=2060x600x250mm

The standard flush-mounting EP system is a system for surface mounting factory finished, type-tested switchgear assemblies

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic empty enclosure Catalog Number 142445 Model Code BPM-F-600/20/2-P-EP EAN 4015081391769 Product Length/Depth 270 mm Product Height 2080 mm Product Width 620 mm Product Weight 47 kg
Compliances RoHS conform Delivery program

Color Gray Technical data - mechanical

Surface finishing Powder coating Mounting method Detached Material Steel Material quality Other Number of connector holes 0 Number of covers/doors 1 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N Permissible load of the mounting plate according to IEC 62208 - max 0 N Installation type Floor installation possible Temperature-rise verification as per IEC 60890 Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 132 W Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 112 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top

(IEC 60890) 265 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 225 W Heat diss. ambient 35°C delta T:20°C free stand individ. encl. top (IEC 60890) 158 W Heat diss. ambient 35°C delta T:20°C free stand starting encl. top (IEC 60890) 144 W Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890) 127 W Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890) 119 W Heat diss. ambient 35°C delta T:35°C free....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-600/20/2-P-EP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.