

INDUSTRIAL COMPONENT DATA

BPM-F-830/20/3-P-IVS 111392 EATON ELECTRIC
Floor-standing distribution board, IVS, IP55, HxWxD
2060x830x320mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-830/20/3-P-IVS



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-830/20/3-P-IVS
Catalog number	111392
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-A23F2FC137
Generated	2026-08-04

Product Overview

Floor-standing distribution board, IVS, IP55, HxWxD=2060x830x320mm

Service distribution boards IVS are used for power distribution and measurement purposes in electrical systems for household electrical systems and in comparative systems such as residential buildings, schools, administration centers, offices and similar buildings.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor-standing distribution board, IVS, IP55, HxWxD=2060x830x320mm Service distribution boards IVS are used for power distribution and measurement purposes in electrical systems for household electrical systems and in comparative systems such as residential buildings, schools, administration centers, offices and similar buildings. Delivery program

Product range Service distribution board IVS Basic function Floor-standing enclosures Single unit/Complete unit Complete housing Degree of Protection IP55 (with door and flange) Description Profi Plus basic enclosures

Monoblock enclosure with door and rotary lever

Including open cable entries top and bottom, prepared for F3A flange

Exchangeable door hinges

Covered hinges

Door opening angle 100° Material Sheet steel Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey Colour light gray (RAL 7035) Information about equipment supplied Including mounting system for the IVS mounting units

including insulating surround and mounted insulated support bracket Width 830 mm Height 2060 mm Depth 320 mm

Technical data

General Standards EN 60439-1/3

IEC 62208 Protection class 1 Degree of Protection IP55 (with door and flange) Power lossMax. admissible heat dissipation, ambient air temperature +35 °C 391 W Weight 71 kg Material characteristics Material Sheet steel Surface treatment

Painting, phosphated and polyester powder coating Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey Colour light gray (RAL 703...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-830/20/3-P-IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.