

INDUSTRIAL COMPONENT DATA

BP-F-1200/17/3-F 120693 Y7-120693 EATON ELECTRIC Floor standing distribution board, flexible surface mountin..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1200/17/3-F



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1200/17/3-F
Catalog number	Y7-120693
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-A05E053514
Generated	2026-08-05

Product Overview

Floor standing distribution board, flexible surface mounting, W = 1200 mm, H = 1760 mm, D = 300 mm

BP-F-1200/17/3-F

Flexible-configuration floor standing distribution board, IP30, gray, RAL 7035, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Floor standing distribution board, flexible surface mounting, W = 1200 mm, H = 1760 mm, D = 300 mmFlexible-configuration floor standing distribution board, IP30, gray, RAL 7035, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result

of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

General specificationsProduct nameEaton xEnergy Basic empty enclosurePart

no.BP-F-1200/17/3-FEAN4015081185238Product Length/Depth315 millimetreProduct height1780 millimetreProduct width1215 millimetreProduct weight51 kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeEmpty enclosureProduct Sub TypeNoneDelivery programTypeBasic deviceApplicationIndoor (installation site)ColorGray

Light gray (RAL 7035)Technical Data - MechanicalSurface finishingPowder coating

With powder coatingMo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1200/17/3-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.