

INDUSTRIAL COMPONENT DATA

BP-F-400/20/3-F 102396 Y7-102396 EATON ELECTRIC Floor standing distribution board, flexible surface mounting..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-400/20/3-F



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-400/20/3-F
Catalog number	Y7-102396
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-C6FCCFA8D8
Generated	2026-08-06

Product Overview

Floor standing distribution board, flexible surface mounting, W = 400 mm, H = 2060 mm, D = 300 mm

BP-F-400/20/3-F

Flexible-configuration floor standing distribution board, IP30, gray, RAL 7035, width 400 mm, outside height 2060 mm, front plate height 1950 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Floor standing distribution board, flexible surface mounting, W = 400 mm, H = 2060 mm, D = 300 mmFlexible-configuration floor standing distribution board, IP30, gray, RAL 7035, width 400 mm, outside height 2060 mm, front plate height 1950 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result

of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

General specificationsProduct nameEaton xEnergy Basic empty enclosurePart

no.BP-F-400/20/3-FEAN4015081022847Product Length/Depth315 millimetreProduct height2080 millimetreProduct width415 millimetreProduct weight28 kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeEmpty enclosureProduct Sub TypeNoneDelivery programTypeBasic deviceApplicationIndoor (installation site)ColorLight gray (RAL 7035)

GrayTechnical Data - MechanicalSurface finishingWith powder coating

Powder coatingMounti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-400/20/3-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.