


INDUSTRIAL COMPONENT DATA

BPM-F-600/17-W 111079 0002459531 EATON ELECTRIC

Floor-standing distribution board with double-bit lock, IP55..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-600/17-W



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-600/17-W
Catalog number	0002459531
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-4C4D17CFFC
Generated	2026-08-06

Product Overview

Floor-standing distribution board with double-bit lock, IP55, HxWxD=1760x600x320mm, white

Floor standing distribution board for damp locations with double-bit lock, IP55, BPM-F-...Width 600 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure with door and double-bit lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame , indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, white, RAL 9016

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor-standing distribution board with double-bit lock, IP55, HxWxD=1760x600x320mm, white EL-Nummer (Norway) 0002459531 Floor standing distribution board for damp locations with double-bit lock, IP55, BPM-F-...Width 600 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure with door and double-bit lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly

configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, white, RAL 9016 [Delivery program

Mounting type Floor standing distribution board Material Sheet steel Door interlock Double-ward lock Installation site Moisture-proof Degree of Protection IP55 Surface finish With powder coating Width 600 mm Depth 320 mm Height 1760 mm Colour white (RAL 9016) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degree...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-600/17-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.