

INDUSTRIAL COMPONENT DATA

BPM-F-400/17-P 111047 Y7-111047 EATON ELECTRIC

Floor-standing distribution board with locking rotary lever, ..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-400/17-P



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-400/17-P
Catalog number	Y7-111047
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-DA2B523E72
Generated	2026-08-06

Product Overview

Floor-standing distribution board with locking rotary lever, IP55, HxWxD=1760x400x320mm

BPM-F-400/17-P

Floor standing distribution board for damp locations with rotary lever, IP55, BPM-F-...-P, width 400 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure with door and roller lever lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame , indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic empty enclosure Catalog Number 111047 Model Code BPM-F-400/17-P EAN

4015081106080 Product Length/Depth 350 mm Product Height 1790 mm Product Width 430 mm Product Weight 44.1 kg

Compliances RoHS conform Delivery program

Type Basic device Application Moisture-proof (installation site) Color Gray

Light gray (RAL 7035) Technical data - mechanical

Surface finishing Powder coating

With powder coating Mounting method Floor standing distribution board

Detached Material Steel

Sheet steel Material quality Other Number of connector holes 0 Number of covers/doors 1 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N

Permissible load of the mounting plate according to IEC 62208 - max 0 N Cover/door type Rotary lever Grade material

Sheet steel Installation type Floor installation possible Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 79 W Heat diss. ambient 35°C delta T: 20°C

wall mount middle encl. top (IEC 60890) 68 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top (IEC

60890) 159 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 136 W Heat diss. ambient

35°C delta T:20°C free stand individ. encl. top (IEC 60890) 106 W Heat diss. ambient 35°C delta T:20°C free stand starting

encl. top (IEC 60890) 94 W Heat diss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-400/17-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.