

INDUSTRIAL COMPONENT DATA

BPM-F-400/20-P 111048 Y7-111048 EATON ELECTRIC

Floor-standing distribution board with locking rotary lever, ..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-400/20-P



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-400/20-P
Catalog number	Y7-111048
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-09CD01D71A
Generated	2026-08-06

Product Overview

Floor-standing distribution board with locking rotary lever, IP55, HxWxD=2060x400x320mm

BPM-F-400/20-P

Floor standing distribution board for damp locations with rotary lever, IP55, BPM-F-...-P, width 400 mm, outside height 2060 mm, front plate height 1950 mm, depth 320 mm, welded enclosure with door and roller lever lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame , indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

Floor-standing distribution board with locking rotary lever, IP55, HxWxD=2060x400x320mmFloor standing distribution board for damp locations with rotary lever, IP55, BPM-F-...-P, width 400 mm, outside height 2060 mm, front plate height 1950 mm, depth 320 mm, welded enclosure with door and roller lever lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame , indoor installation with MSW or

mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

General specificationsProduct nameEaton xEnergy Basic empty enclosurePart

no.BPM-F-400/20-PEAN4015081106097Product Length/Depth350 millimetreProduct height2090 millimetreProduct width430 millimetreProduct weight50.6 kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeEmpty enclosureProduct Sub TypeNoneDelivery programTypeBasic deviceApplicationMoisture-proof (installation site)ColorGray

Light gray (RAL 7035)Technical Data - MechanicalS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-400/20-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.