

INDUSTRIAL COMPONENT DATA

BP-F-1000/17/3-P 102361 XTCE032C10G2 EATON ELECTRIC

Floor standing distribution board with locking rotary le..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1000/17/3-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1000/17/3-P
Catalog number	XTCE032C10G2
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-F48784A410
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 1000 mm, H = 1760 mm, D = 300 mm
Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 1000 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with rotary lever, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic LV systems Low voltage switchgear Catalog Number 102361 Model Code BP-F-1000/17/3-P EAN 4015081022496 Product Length/Depth 315 mm Product Height 1780 mm Product Width 1015 mm Product Weight 62 kg Compliances RoHS conform Delivery program Type Basic device Application Indoor (installation site) Color Gray Light gray (RAL 7035) Technical data - mechanical Surface finishing With powder coating

Powder coating Mounting method Floor standing distribution board

Detached Material Sheet steel

Steel Material quality Other Number of connector holes 0 Number of covers/doors 2 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N

Permissible load of the mounting plate according to IEC 62208 - max 0 N Cover/door type Rotary lever Grade material

Sheet steel Installation type Floor installation possible Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 216 W Heat diss. ambient 35°C delta T:

20°C wall mount middle encl. top (IEC 60890) 204 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top

(IEC 60890) 434 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 410 W Heat diss.

ambient 35°C delta T:20°C free stand individ. encl. top (IEC 60890) 227 W Heat diss. ambient 35°C delta T:20°C free stand

starting encl. top (IEC 60890) 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1000/17/3-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.