

INDUSTRIAL COMPONENT DATA

BP-F-1200/20/4-P 119196 0002460728 EATON ELECTRIC Floor standing distribution board with locking rotary leve..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1200/20/4-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1200/20/4-P
Catalog number	0002460728
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-6062262CC7
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 1200 mm, H = 2060 mm, D = 400 mm

Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 1200 mm, outside height 2060 mm, front plate height 1950 mm, depth 400 mm, includes top and bottom gland plate inserts, metal door with rotary lever, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured , multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic empty enclosure Catalog Number 119196 Model Code BP-F-1200/20/4-P EAN

4015081173334 Product Length/Depth 415 mm Product Height 2080 mm Product Width 1215 mm Product Weight 100 kg

Compliances RoHS conform Delivery program

Type Basic device Application Indoor (installation site) Color Light gray (RAL 7035)

Gray Technical data - mechanical

Surface finishing Powder coating

With powder coating Mounting method Floor standing distribution board

Detached Material Sheet steel

Steel Material quality Other Number of connector holes 0 Number of covers/doors 2 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N Permissible load of the mounting plate according to IEC 62208 - max 0 N Cover/door type Rotary lever Grade material Sheet steel Installation type Floor installation possible Temperature-rise verification as per IEC 60890 Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 301 W Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 282 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top (IEC 60890) 604 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 565 W Heat diss. ambient 35°C delta T: 20°C free stand individ. encl. top (IEC 60890) 311 W Heat diss. ambient 35°C delta T: 20°C free stand starting encl. top (IEC 60890) 306 W Heat diss. a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1200/20/4-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.