

INDUSTRIAL COMPONENT DATA

BP-F-400/20/3-P 102356 D02-LTS/20/3-R EATON ELECTRIC

Floor standing distribution board with locking rotary I..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-400/20/3-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-400/20/3-P
Catalog number	D02-LTS/20/3-R
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-9C67D90C71
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 400 mm, H = 2060 mm, D = 300 mm

Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 400 mm, outside height 2060 mm, front plate height 1950 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with rotary lever, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

D02 switch-disconnectors, 20A, 400V, 3 p Eaton Catalog No. D02-LTS/20/3-R The flash function indicates the blowing of fuse link, with fixed (non-removable) adapter sleeves, 3 installed fuse links and 2 fuse dummies for single-phase application, contact position indicator, fuse plug without screw cap, switches the load on all poles and without touching by hand, sealable and lockable [Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D0-system switch disconnecter (EC000277) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed switch disconnecter () [AKE282013]) Number of poles 3 Construction size D02 Rated voltage 400 V Rated current 20 A]

ETIM for 102356 Cabinets and enclosures (EC000261)

Feature Name

Feature Value

Width (EF000008)

415 mm

Height (EF000040)

2080 mm

Depth (EF000049)

315 mm

Material (EF002169)

Steel

Material quality (EF001257)

Other

Surface finishing (EF006569)

Powder coated

Colour (EF000007)

Grey

RAL-number (EF000116)

7035

Freestanding (EF020363)

Yes

Floor standing wall model (EF015208)

No

Suitable for wall mounting (EF000664)

No

Corner model (EF020814)

No

Intermediate mounting (EF022994)

No

Couplable (EF001229)

No

With mounting plate (EF000118)

No

Mounting plate depth-adjustable (EF006054)

Yes

Suitable for wall built-in (EF007536)

No

Pole fastening (EF009582)

No

With door (EF009169)

Yes

Number of doors (EF000122)

1

With glazed door (EF001089)

No

With venti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-400/20/3-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.