

INDUSTRIAL COMPONENT DATA

BP-F-600/17/3-P 102357 XTCE032C10G2 EATON ELECTRIC

Floor standing distribution board with locking rotary lev..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-600/17/3-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-600/17/3-P
Catalog number	XTCE032C10G2
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-B50FF20549
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 600 mm, H = 1760 mm, D = 300 mm

Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 600 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with rotary lever, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Contactor, 3p+1N/O, 15kW/400V/AC3 Eaton Catalog No. XTCE032C10G2 Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 32 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 45 A, enclosed: I_{th} = 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole

open: Ith= 100 A, enclosed: Ith= 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 10 kW, 380 V 400 V: P= 15 kW, 660 V 690 V: P= 17 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 4 kW, 380 V 400 V: P= 7 kW, 660 V 690 V: P= 10 kW, Can be combined with auxiliary contact: DILM32-XHI..., DILA-XHI(V)..., Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation [Delivery program Product range Contactors Application Contactors for Motors Subrange Contactors up to 170 A, 3 pole Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-600/17/3-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.