

INDUSTRIAL COMPONENT DATA

BP-F-600/20/4-P 119193 EATON ELECTRIC Floor standing distribution board with locking rotary lever, W 600 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-600/20/4-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-600/20/4-P
Catalog number	119193
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-8F9E41194B
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 600 mm, H = 2060 mm, D = 400 mm

Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 600 mm, outside height 2060 mm, front plate height 1950 mm, depth 400 mm, includes top and bottom gland plate inserts, metal door with rotary lever, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured , multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

Trip indicator kit, high speed, 1.5 A, AC 690 V, FM, BS, indicating Fuse accessory, Trip indicator kit, high speed, 1.5 A, AC 690 V, FM, BS, with indicator, Attaches in parallel to main fuse-link. Can be used to operate a microswitch (available separately) to provide remote indication, FM, BS88-4, Breaking Capacity 100 kA, Optional accessories microswitch MAI, Supplied with TI600 trip indicator and two clips [Delivery program

Product range Fuse accessory Basic function Trip indicator kit Field of application high speed Rated current [I] 1.5 A Rated voltage AC 690 V Construction size FM Status indicator with indicator Description Attaches in parallel to main fuse-link. Can be used to operate a microswitch (available separately) to provide remote indication Breaking Capacity 100 kA usable for size/applications FM Standard/Approval BS Standards/Regulations BS88-4 Optional accessories microswitch MAI Supplied with TI600 trip indicator and two clips , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Accessories for Low Voltage HRC fuse (EC001659) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low Voltage HRC fuse (accessories) ( [ACN536011]) Construction size Other Type of accessory Other]
ETIM for 119193 Cabinets and enclosures (EC000261)

Feature Name

Feature Value

Width (EF000008)

615 mm

Height (EF000040)

2080 mm

Depth (EF000049)

415 mm

Material (EF002169)

Steel

Material q...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-600/20/4-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.