

INDUSTRIAL COMPONENT DATA

BP-F-800/20/3-P 102360 XTMF9A00AD EATON ELECTRIC

Floor standing distribution board with locking rotary lever..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-800/20/3-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-800/20/3-P
Catalog number	XTMF9A00AD
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-4507781621
Generated	2026-08-05

Product Overview

Floor standing distribution board with locking rotary lever, W = 800 mm, H = 2060 mm, D = 300 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

4 pole contactor, 20A/AC-1, DC operated Eaton Catalog No. XTMF9A00AD Contactor, Application: Mini Contactors for Motors and Resistive Loads, DILEM contactors, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Number of poles: 4 pole, Rated operational current AC-3 380 V 400 V: I_{le} = 9 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 22 A, enclosed: I_{th} = 16 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 60 A, enclosed: I_{th} = 50 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 4 kW, 660 V 690 V: P = 4 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1.5 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 3 kW, For use with: ...DILEM, ...DILE, Voltage AC/DC: DC operation [Delivery program

Product range Contactors Application Mini Contactors for Motors and Resistive Loads Subrange DILEM contactors

Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces

NAC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Connection technique Screw terminals Number of poles 4 pole Rated oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-800/20/3-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.