

INDUSTRIAL COMPONENT DATA

BP-F-800/20/4-P 119194 0002460726 EATON ELECTRIC Floor standing distribution board with locking rotary lever..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-800/20/4-P



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-800/20/4-P
Catalog number	0002460726
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-BEEFB7C090
Generated	2026-08-06

Product Overview

Floor standing distribution board with locking rotary lever, W = 800 mm, H = 2060 mm, D = 400 mm

Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 800 mm, outside height 2060 mm, front plate height 1950 mm, depth 400 mm, includes top and bottom gland plate inserts, metal door with rotary lever, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured , multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor standing distribution board with locking rotary lever, W = 800 mm, H = 2060 mm, D = 400 mm EL-Nummer (Norway) 0002460726 Floor standing distribution board with locking rotary lever, IP30, gray, RAL 7035, width 800 mm, outside height 2060 mm, front plate height 1950 mm, depth 400 mm, includes top and bottom gland plate inserts, metal door with rotary lever, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure [Delivery program Mounting type Floor standing distribution board Material Sheet steel Door interlock Rotary lever Installation site Indoor Degree of Protection IP30 Surface finish With powder coating Width 800 mm Depth 400 mm Height 2060 mm Colour light

gray (RAL 7035) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 240 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure, free...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-800/20/4-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.