

INDUSTRIAL COMPONENT DATA

BP-F-1000/20/2,5 119190 EATON ELECTRIC Feed-in terminals 2,5-16qmm for PXS24-BB

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1000/20/2,5



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1000/20/2,5
Catalog number	119190
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-047956711C
Generated	2026-08-05

Product Overview

Feed-in terminals 2,5-16qmm for PXS24-BB

Floor standing distribution board with three-point turn-lock, W = 1000 mm, H = 2060 mm, D = 250 mm

Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 1000 mm, outside height 2060 mm, front plate height 1950 mm, depth 250 mm, includes top and bottom gland plate inserts, metal door with cam lock, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured , multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor standing distribution board with three-point turn-lock, W = 1000 mm, H = 2060 mm, D = 250 mm Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 1000 mm, outside height 2060 mm, front plate height 1950 mm, depth 250 mm, includes top and bottom gland plate inserts, metal door with cam lock, door can be right-hand or left-hand door, mounting frame (on the back) without mounting rails, suitable only for MSW assembly configuration (no BPZ-CTS-S corner towers required), earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure Delivery program

Mounting type Floor standing distribution board Material Sheet steel Door interlock Three-point turn-lock Installation site

Indoor Degree of Protection IP30 Surface finish With powder coating Width 1000 mm Depth 250 mm Height 2060 mm
Colour light gray (RAL 7035) Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 233 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure, free-standing [PV] 227 W Heat dissipation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1000/20/2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.