

INDUSTRIAL COMPONENT DATA

BP-F-1200/17/3 102323 0002459181 EATON ELECTRIC Floor standing distribution board with three-point turn-lock..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1200/17/3



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1200/17/3
Catalog number	0002459181
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-0555FDD59E
Generated	2026-08-06

Product Overview

Floor standing distribution board with three-point turn-lock, W = 1200 mm, H = 1760 mm, D = 300 mm

Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with cam lock, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Floor standing distribution board with three-point turn-lock, W = 1200 mm, H = 1760 mm, D = 300 mm EL-Nummer (Norway) 0002459181 Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with cam lock, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required. indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior

fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure [Delivery program

Mounting type Floor standing distribution board Material Sheet steel Door interlock Three-point turn-lock Installation site

Indoor Degree of Protection IP30 Surface finish With powder coating Width 1200 mm Depth 300 mm Height 1760 mm

Colour light gray (RAL 7035) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1200/17/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.