

INDUSTRIAL COMPONENT DATA

BP-F-400/17/3 102055 0002459172 EATON ELECTRIC Floor standing distribution board with three-point turn-lock,..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-400/17/3



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-400/17/3
Catalog number	0002459172
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-27A423D527
Generated	2026-08-06

Product Overview

Floor standing distribution board with three-point turn-lock, W = 400 mm, H = 1760 mm, D = 300 mm
Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 400 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with cam lock, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-holder, low voltage, 125 A, AC 690 V, 22 x 58 mm, 3P, IEC, UL, with microswitch Fuse accessory, Fuse-holder, low voltage, 125 A, AC 690 V, 22 x 58 mm, 3P, IEC, UL, with microswitch, C22M and C22G fuses, IEC 60269-1, IEC 60269-2, IP20 [Delivery program

Product range Fuse accessory Basic function Fuse-holder Field of application low voltage Rated current [I] 125 A Rated voltage AC 690 V Size 22 x 58 mm Description with microswitch Protection IP20 Number of poles 3P usable for size/applications C22M and C22G fuses Standard/Approval IEC

UL Standards/Regulations IEC 60269-1

IEC 60269-2 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse ( [ADI305007]) Nominal voltage 690 V Mounting method DIN rail For fuse size 22x58 mm Number of poles 3 Concurrently switching N-neutral No Lockable Yes Optical defect indication No Width in number of modular spacings 6 Built-in depth 51.5 mm Degree of protection (IP) IP20]

ETIM for 102055 Cabinets and enclosures (EC000261)

Feature Name

Feature Value

Width (EF000008)

415 mm

Height (EF000040)

1780 mm

Depth (EF000049)

315 mm

Material (EF002169)

Steel

Material quality (EF001257)

Other

Surface finishing (EF006569)

Powder coating

Colour (EF000007)

Grey

RAL-number (EF000116)

7035

Freestanding (EF020363)

true

Floor standing wall model...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-400/17/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.