

INDUSTRIAL COMPONENT DATA

BP-F-600/20/3 102058 0002459175 EATON ELECTRIC Floor standing distribution board with three-point turn-lock,..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-600/20/3



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-600/20/3
Catalog number	0002459175
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-F50ED9C6DB
Generated	2026-08-05

Product Overview

Floor standing distribution board with three-point turn-lock, W = 600 mm, H = 2060 mm, D = 300 mm

Floor standing distribution board with cam lock, IP30, gray, RAL 7035, width 600 mm, outside height 2060 mm, front plate height 1950 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with cam lock, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, low voltage, 600 A, AC 300 V, DC 160 V, 77.8 x 31.8, T, UL, very fast acting Fuse, Fuse-link, low voltage, 600 A, AC 300 V, DC 160 V, 77.8 x 31.8, T, UL, very fast acting, Breaking Capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 600 A Rated voltage DC 160 V Size 77.8 x 31.8 Utilization category T Breaking Capacity 20 kA Release characteristic [class] very fast acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 600 A Rated voltage 300 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No] ETIM for 102058 Cabinets and enclosures (EC000261)

Feature Name

Feature Value

Width (EF000008)

615 mm

Height (EF000040)

2080 mm

Depth (EF000049)

315 mm

Material (EF002169)

Steel

Material quality (EF001257)

Other

Surface finishing (EF006569)

Powder coated

Colour (EF000007)

Grey

RAL-number (EF000116)

7035

Freestanding (EF020363)

Yes

Floor standing wall model (EF015208)

No

Suitable for wall mounting (EF000664)

No

Corner model (EF020814)

No

Intermediate mounting (EF022994)

No

Couplable (EF001229)

No

With mounting plate (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-600/20/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.