

INDUSTRIAL COMPONENT DATA

BPM-F-1000/17-F 174370 0002455731 EATON ELECTRIC

Floor-standing distribution board without door, IP55, HxWxD..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-1000/17-F



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-1000/17-F
Catalog number	0002455731
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-713D1D00F1
Generated	2026-08-06

Product Overview

Floor-standing distribution board without door, IP55, HxWxD=1760x1000x320mm

Floor standing distribution board for damp locations without door, IP55, BPM-F-...Width 1000 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible , if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER**

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic empty enclosure Catalog Number 174370 Model Code BPM-F-1000/17-F EAN

4015081708321 Product Length/Depth 320 mm Product Height 1760 mm Product Width 1000 mm Product Weight 54.1 kg

Compliances RoHS conform Delivery program

Type Basic device Application Moisture-proof (installation site) Color Gray

Light gray (RAL 7035) Technical data - mechanical

Surface finishing Powder coating

With powder coating Mounting method Floor standing distribution board

Detached Material Sheet steel

Steel Material quality Other Number of connector holes 0 Number of covers/doors 0 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N

Permissible load of the mounting plate according to IEC 62208 - max 0 N Grade material Sheet steel Installation type Floor installation possible Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 222 W Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 215 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top (IEC 60890) 445 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 431 W Heat diss. ambient 35°C delta T: 20°C free stand individ. encl. top (IEC 60890) 234 W Heat diss. ambient 35°C delta T: 20°C free stand starting encl. top (IEC 60890) 228 W Heat diss. ambient 35°C delta T: 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-1000/17-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.