

INDUSTRIAL COMPONENT DATA

BPM-F-600/17-F 174362 Y7-174362 EATON ELECTRIC

Floor-standing distribution board without door, IP55, HxWxD 1..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-600/17-F



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-600/17-F
Catalog number	Y7-174362
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-D7635338DB
Generated	2026-08-06

Product Overview

Floor-standing distribution board without door, IP55, HxWxD=1760x600x320mm

Floor distribution cabinet without door, IP55, HxWxD=1760x600x320mm

Floor standing distribution board for damp locations without door, IP55, BPM-F-...Width 600 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Floor-standing distribution board without door, IP55, HxWxD=1760x600x320mmFloor standing distribution board for damp locations without door, IP55, BPM-F-...Width 600 mm, outside height 1760 mm, front plate height 1650 mm, depth 320 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or

left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible , if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

General specificationsProduct nameEaton xEnergy Basic LV systems Low voltage switchgearPart no.BPM-F-600/17-FEAN4015081708246Product Length/Depth320 millimetreProduct height1760 millimetreProduct width600 millimetreProduct weight46.8 kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeLV systemsProduct Sub TypeLow voltage switchgearDelivery programTypeBasic deviceApplicationMoisture-proof (installation site)ColorGray

Light gray (RAL 7035)Technical Data - MechanicalSurface finishingPowder....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-600/17-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.