

INDUSTRIAL COMPONENT DATA

BPM-F-800/20-F 174368 Y7-174368 EATON ELECTRIC

Floor-standing distribution board without door, IP55, HxWxD 2..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-F-800/20-F



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-F-800/20-F
Catalog number	Y7-174368
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-AD3412C640
Generated	2026-08-06

Product Overview

Floor-standing distribution board without door, IP55, HxWxD=2060x800x320mm

Floor standing distribution board for damp locations without door, IP55, BPM-F-...Width 800 mm, outside height 2060 mm, front plate height 1950 mm, depth 320 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible , if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

EL-Nummer (Norway)2455729Floor-standing distribution board without door, IP55, HxWxD=2060x800x320mmFloor standing distribution board for damp locations without door, IP55, BPM-F-...Width 800 mm, outside height 2060 mm, front plate height 1950 mm, depth 320 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door, ample wiring area, open cable entries on top and bottom, prepared for F3A gland

plate insert, variable interior fittings with / without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035 Delivery program

Mounting type Floor standing distribution board Material Sheet steel Installation site Moisture-proof Degree of Protection IP55 Surface finish With powder coating Width 800 mm Depth 320 mm Height 2060 mm Colour light gray (RAL 7035) Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure, free-standing [PV] 214 W Heat dissip...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-F-800/20-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.