

INDUSTRIAL COMPONENT DATA

M22-E2 216543 Y7-216543 EATON ELECTRIC Flush mounting plate, 2 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: M22-E2



Manufacturer	EATON - MOELLER
MPN / Reference	M22-E2
Catalog number	Y7-216543
Category	Built-in panel for command devices
Minimum order	5 Pcs
Document ID	EO-6D901C5B04
Generated	2026-08-03

Product Overview

Flush mounting plate, 2 mounting locations

M22-E2

Eaton Moeller® series M22 Flush mounting plate, 2 mounting locations

Flush mounting plate, Number of locations: 2, Degree of Protection: IP65, Color grey, Color RAL Value: RAL 7035, Connection to SmartWire-DT: no, No legend plates possible with vertical arrangements, Degree of protection only in conjunction with a suitable enclosure and correct mounting., Aluminum light anodized, including M22-XE...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Flush mounting plate Catalog Number 216543 Model Code M22-E2
EAN 4015082165437 Product Length/Depth 3 mm Product Height 72 mm Product Width 105 mm Product Weight 0.076 kg
Compliances CE Marked Certifications EN 60947-5

IEC 60947-5

CSA Std. C22.2 No. 14-05

CSA Std. C22.2 No. 94-91

UL 508

VDE

CSA

CSA File No.: 012528

CSA-C22.2 No. 14-05

UL File No.: E29184

CE

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

IEC/EN 60947-5

UL Features & Functions

Color Gray Material Aluminum Number of locations 2 RAL-number 7035 General

Degree of protection IP65

Only in conjunction with a suitable enclosure and correct mounting

NEMA 4X, 13 Opening diameter 22 mm Type Surface mounting enclosure Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-E2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.