

**INDUSTRIAL COMPONENT DATA**

# M22-E4 216545 Y7-216545 EATON ELECTRIC Flush mounting plate, 4 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: M22-E4



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | M22-E4                             |
| Catalog number  | Y7-216545                          |
| Category        | Built-in panel for command devices |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-952B37EBBE                      |
| Generated       | 2026-08-01                         |

## Product Overview

Flush mounting plate, 4 mounting locations

M22-E4

Eaton Moeller® series M22 Flush mounting plate, 4 mounting locations

Flush mounting plate, Number of locations: 4, Degree of Protection: IP65, Color grey, Color RAL Value: RAL 7035, Connection to SmartWire-DT: no, No legend plates possible with vertical arrangements, Degree of protection only in conjunction with a suitable enclosure and correct mounting., Aluminum light anodized, including M22-XE...

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Flush mounting plate Catalog Number 216545 Model Code M22-E4  
EAN 4015082165451 Product Length/Depth 3 mm Product Height 72 mm Product Width 171 mm Product Weight 0.161 kg  
Certifications CE

CSA Class No.: 3211-03

IEC/EN 60947-5

UL File No.: E29184

CSA-C22.2 No. 94-91

CSA File No.: 012528

UL 508

CSA

CSA-C22.2 No. 14-05

UL

UL Category Control No.: NKCR Features & Functions

Color Gray Material Aluminum Number of locations 4 RAL-number 7035 General

Degree of protection IP65

Only in conjunction with a suitable enclosure and correct mounting

NEMA 4X, 13 Opening diameter 22 mm Type Surface mounting enclosure Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Contacts

Force for positive opening - min 0 N Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole,

current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation,

non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-E4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.