

INDUSTRIAL COMPONENT DATA

E8 054423 Y7-54423 EATON ELECTRIC Flush mounting plate, gray, 8 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: E8



Manufacturer	EATON - MOELLER
MPN / Reference	E8
Catalog number	Y7-54423
Category	Built-in panel for command devices
Minimum order	1 Pcs
Document ID	EO-B40486202B
Generated	2026-08-01

Product Overview

Flush mounting plate, gray, 8 mounting locations

8-hole recessed keypad Grey For RMQ16

Flush mounting plate, Single unit, Number of locations: 8, Degree of Protection: IP65, Color Color Enclosure cover light grey (RAL 7035), Connection to SmartWire-DT: no, for conventional wiring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Flush mounting plate, gray, 8 mounting locationsFlush mounting plate, Single unit, Number of locations: 8, Degree of Protection: IP65, Color Color Enclosure cover light grey (RAL 7035), Connection to SmartWire-DT: no, for conventional wiring

General specificationsProduct nameEaton Moeller® series RMQ16 Accessory Flush mounting platePart no.E8EAN4015080544234Product Length/Depth20 millimetreProduct height100 millimetreProduct width136 millimetreProduct weight0.122 kilogramCertificationsCSA Class No.: 3211-03

UL

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

UL File No.: E29184

CSA

UL 508

IEC/EN 60947-5

CE

CSA File No.: 46552 Product Tradename RMQ16 Product Type Accessory Product Sub Type Flush mounting plate Features & Functions Color Gray Enclosure color Light gray, Cover (RAL 7035) Functions For conventional wiring Material Plastic Number of locations 8 General information Degree of protection NEMA 1

IP65 Opening diameter 16 mm Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Communication Connection to SmartWire-DT No Design verification Equipment heat dissipation, current-dependent P_{vid0 W} Heat dissipation capacity P_{diss0 W} Heat dissipation per pole, current-dependent P_{vid0 W} Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs0 W} 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.