INDUSTRIAL COMPONENT DATA

E8 054423 Y7-54423 EATON ELECTRIC Flush mounting plate, gray, 8 mounting locations

Brand: EATON - MOELLER | Manufacturer Part Number: E8

Manufacturer	EATON - MOELLER
MPN / Reference	E8
Catalog number	Y7-54423
Category	Built-in panel for command devices
Minimum order	1 Pcs
Document ID	EO-B40486202B
Generated	2026-08-04

Product Overview

Flush mounting plate, gray, 8 mounting locations
8-hole recessed keypad Grey For RMQ16
Flush mounting plate, Single unit, Number of locations: 8, Degree of Protection: IP65, Color Color Enclosure cover light grey (RAL 7035), Connection to SmartWire-DT: no, for conventional wiring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Flush mounting plate, gray, 8 mounting locationsFlush mounting plate, Single unit, Number of locations: 8, Degree of Protection: IP65, Color Color Enclosure cover light grey (RAL 7035), Connection to SmartWire-DT: no, for conventional wiring
General specificationsProduct nameEaton Moeller® series RMQ16 Accessory Flush mounting platePart no.E8EAN4015080544234Product Length/Depth20 millimetreProduct height100 millimetreProduct width136 millimetreProduct weight0.122 kilogramCertificationsCSA Class No.: 3211-03
UL
CSA-C22.2 No. 14-05
UL Category Control No.: NKCR
UL File No.: E29184
CSA
UL 508

IEC/EN 60947-5
CE
CSA File No.: 46552Product TradenameRMQ16Product TypeAccessoryProduct Sub TypeFlush mounting plateFeatures & FunctionsColorGrayEnclosure colorLight gray, Cover (RAL 7035)FunctionsFor conventional wiringMaterialPlasticNumber of locations8General informationDegree of protectionNEMA 1
IP65Opening diameter16 mmClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max60 °CCommunicationConnection to SmartWire-DTNoDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdiss0 WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified heat dissipation (In)0 AStatic heat dissipation, non-current-dependent Pvs0 W10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.