

INDUSTRIAL COMPONENT DATA

KLV-2UPP-4PR 178867 Y7-178867 EATON ELECTRIC For indoors, flush-mounting, double-row form of delivery for pr..

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-2UPP-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-2UPP-4PR
Catalog number	Y7-178867
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-1F01A323FD
Generated	2026-08-05

Product Overview

For indoors, flush-mounting, double-row; form of delivery for projects

KLV-2UPP-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. For indoors, flush-mounting, double-row, form of delivery for projects

Form of delivery for projects: Indoors flush mounting expansion kit for second generation KLV compact distribution boards, equipment supplied: device carrier, front cover, neutral and protective conductor terminals with KSK plug-in terminal technology, cable retainer, installation instructions, label sheet. Standards: Complete distribution board in accordance with IEC/EN 60670-24, DIN 43871, IEC/EN 62208 and, accordingly, approved for distribution boards as defined in IEC/EN 61439-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Compact Distribution Boxes
--------------	--

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 178867 Model Code KLV-2UPP-4PR EAN 4015081741960 Product Length/Depth 40 mm Product Height 387.5 mm Product Width 274 mm Product Weight 0.85 kg

Compliances RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Delivery program

Type Accessory/spare part type Other

Accessory Application Indoor (installation site) Color Traffic white (RAL 9016) Technical data - electrical

Frequency rating 50 Hz Technical data - mechanical

Mounting method Flush mounting Material Polystyren (plastic)
Sheet steel, powder-coated Number of module space units per row 12 Number of rows 2 Terminal type Plug-in terminals
PE and N terminal number and cross section PE: 2 x (2.5 mm² - 25 mm²) + 14 x (0.5 mm² - 4 mm²)
N - Fi: 1 x (2.5 mm² - 25 mm²) + 7 x (0.5 mm² - 4 mm²)
N: 2 x (2.5 mm² - 25mm²) + 14 x (0.5 mm² - 4 mm²) Cover/door color White Installation type Flush mounting Module rack
type Rail frame Protective shrouding material Plastic Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature details -5 °C - 40 °C Additional information
Fitted with: Front cover
Neutral-/protective conductor terminal
Installation instructions
Imprintable sheet
Cable retainer
Device support rails Functions Basic device
Additional equipment Protection class II (totally insulated) Special features IP30
Protection Class II
Plastic housing
Used with Basic device
Installation distribution boards
KL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-2UPP-4PR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.