

INDUSTRIAL COMPONENT DATA

KLV-1UPP-4PR 178866 Y7-178866 EATON ELECTRIC For indoors, flush-mounting, single-row form of delivery for pr..

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-1UPP-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-1UPP-4PR
Catalog number	Y7-178866
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-1DB2C2B09D
Generated	2026-08-04

Product Overview

For indoors, flush-mounting, single-row; form of delivery for projects

KLV-1UPP-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. For indoors, flush-mounting, single-row, form of delivery for projects

Form of delivery for projects: Indoors flush mounting expansion kit for second generation KLV compact distribution boards, equipment supplied: device carrier, front cover, neutral and protective conductor terminals with KSK plug-in terminal technology, cable retainer, installation instructions, label sheet. Standards: Complete distribution board in accordance with IEC/EN 60670-24, DIN 43871, IEC/EN 62208 and, accordingly, approved for distribution boards as defined in IEC/EN 61439-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Compact Distribution Boxes
--------------	--

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 178866 Model Code KLV-1UPP-4PR EAN 4015081741953 Product Length/Depth 40 mm Product Height 262.5 mm Product Width 274 mm Product Weight 0.6 kg

Compliances RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Product specifications

Special features IP30Protection Class IIPlastic housing Type Basic deviceInstallation distribution boardsKLV for projects

Accessory/spare part type Other

Accessory Fitted with: Cable retainer

Imprintable sheet

Front cover

Installation instructions

Device support rails

Neutral-/protective conductor terminal Frequency rating 50 Hz Used with KLV for projects

Installation distribution boards

Basic device Color Traffic white (RAL 9016) Degree of protection IP30

IK05 (impact resistance) Terminal type Plug-in terminals Ambient operating temperature details -5 °C - 40 °C Application

Indoor (installation site) Cover/door color White Material Polystyren (plastic)

Sheet steel, powder-coated Number of rows 1 Installation type Flush mounting Mounting method Flush mounting Functions

Basic device

Additional equipment Module rack type Single-rail Number of module space units per row 12 Protection class II (totally insulated) Protective shrouding material Plastic PE and N terminal number and cross section PE: 2 x (2.5 mm² - 25 mm²) + 14 x (0.5 mm² - 4 mm²)

N: 2 x (2.5 mm² - 25mm²) + 14 x (0.5 mm² - 4 mm²)

ETIM for 178866 Distribution boards (EC002287)

Feature Name....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-1UPP-4PR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.