

INDUSTRIAL COMPONENT DATA

KLV-SF3-4PR 178880 Y7-178880 EATON ELECTRIC For outdoors, flush-mounting/hollow-wall mounting, 3-row form of..

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-SF3-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-SF3-4PR
Catalog number	Y7-178880
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-64C6077293
Generated	2026-08-05

Product Overview

For outdoors, flush-mounting/hollow-wall mounting, 3-row; form of delivery for projects

KLV-SF3-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. For outdoors, flush-mounting/hollow-wall mounting, 3-row, form of delivery for projects, SF3-4PR

Form of delivery for projects: Outdoors expansion kit for second generation KLV compact distribution boards, one-of-a-kind super-slim door frame design, optional door with frame with requested RAL color, equipment supplied: door with door frame, 3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm . Standards: Complete distribution board in accordance with IEC/EN 60670-24, DIN 43871, IEC/EN 62208 and, accordingly, approved for distribution boards as defined in IEC/EN 61439-3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 178880 Model Code KLV-SF3-4PR EAN 4015081742097 Product Length/Depth 32 mm Product Height 590 mm Product Width 360 mm Product Weight 3.1 kg
Compliances RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Product specifications
Special features IP30Protection Class IISheet steel door, white (RAL 9016) Type Basic deviceInstallation distribution

boardsKLV for projects Accessory/spare part type Other

Accessory Fitted with: Installation instructions

Door frame with door

3D adjustment element for mounting Frequency rating 50 Hz Used with Basic device

Installation distribution boards

KLV for projects Color Traffic white (RAL 9016) Degree of protection IK05 (impact resistance)

IP30 Ambient operating temperature details -5 °C - 40 °C Application Indoor (installation site) Cover/door color White

Material Sheet steel, powder-coated Number of rows 3 Installation type Hollow-wall mounting and flush mounting Mounting method Hollow wall

Flush mounting Functions Basic device

Additional equipment Number of module space units per row 12 Protection class II (totally insulated) Protective shrouding material Plastic

ETIM for 178880 Distribution boards (EC002287)

Feature Name

Feature Value

Type of accessory/spare part (EF000215)

Other

Accessory (EF013236)

Yes

Spare part (EF013237)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-SF3-4PR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.