


INDUSTRIAL COMPONENT DATA

Z-GSV-10/1P+N/12-O 274402 Y7-274402 EATON ELECTRIC

Phase busbar, 2-phases, 10qmm, fork connector+pin, 12SU

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GSV-10/1P+N/12-O



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GSV-10/1P+N/12-O
Catalog number	Y7-274402
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-224C43B46B
Generated	2026-08-05

Product Overview

Phase busbar, 2-phases, 10qmm, fork connector+pin, 12SU

Z-GSV-10/1P+N/12-O

Block busbar for PLN. (1 space units) + residual current circuit-breakers, supplied with end caps

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Modular Switchgear - Others and Accessories**

Additional Product Information

Phase busbar, 2-phases, 10qmm, fork connector+pin, 12SUBlock busbar for PLN. (1 space units) + residual current circuit-breakers, supplied with end capsTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar

( [ACN992011])Number of phases2Number of poles1Suitable for number of devices11Pitch

dimensions17.95 mmCross section10 mm²Length215 mmNumber of modular spacings12Rated permanent current Iu50

AType of electric connectionOtherInsulatedYesRated surge voltage0 kVConditioned rated short-circuit current Iq25 kA

Max. rated operation voltage Ue415 VRated short-time withstand current Icw0 kASuitable for devices with N-busbarYesSuitable

for devices with auxiliary switchNo

ETIM for 274402 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2
Number of poles (EF001391)
1
Suitable for number of devices (EF007241)
13
Module width (EF007504)
17.95 mm
Cross section (EF000649)
10 mm²
Length (EF001438)
32 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
12
Rated permanent current I_u (EF001389)
50 A
Type of electric connection (EF003961)
Other
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
0 kV
Conditioned rated short-circuit current I_q (EF001444)
25 kA
Max. rated operation volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GSV-10/1P+N/12-O with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.