

INDUSTRIAL COMPONENT DATA

Z-GSV-10/3P+N/12-U 274400 Y7-274400 EATON ELECTRIC

Phase busbar, 4-phases, 10qmm, fork connector+pin, 12SU

Brand: EATON - MOELLER | Manufacturer Part Number: Z-GSV-10/3P+N/12-U



Manufacturer	EATON - MOELLER
MPN / Reference	Z-GSV-10/3P+N/12-U
Catalog number	Y7-274400
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-9F9BE7D0E6
Generated	2026-08-05

Product Overview

Phase busbar, 4-phases, 10qmm, fork connector+pin, 12SU

Z-GSV-10/3P+N/12-U

Eaton Distribution parts. Phase busbar, 4-phases, 10qmm, fork connector+pin, 12SU

Block busbar for PLN. (1 space units) + residual current circuit-breakers, supplied with end caps

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 274400 Model Code Z-GSV-10/3P+N/12-U EAN 4015082744007

Product Length/Depth 32 mm Product Height 23 mm Product Width 217 mm Product Weight 0.121 kg Compliances RoHS

conform Product specifications

Features Insulated

Can be cut to size Electric connection type Other Rated surge voltage 0 kV Rated uninterrupted current (Iu) 50 A Suitable for number of devices 4 Number of poles Three-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 12 Number of phases 4 Pitch dimensions 17.95 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 25 kA Suitable for 9 devices

Devices with N-busbar

ETIM for 274400 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

4

Number of poles (EF001391)

3

Suitable for number of devices (EF007241)

4

Module width (EF007504)

17.95 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

32 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

12

Rated permanent current I_u (EF001389)

50 A

Type of electric connection (EF003961)

Other

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I_q (EF001444)

25 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

Yes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-GSV-10/3P+N/12-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.