


INDUSTRIAL COMPONENT DATA

Z-SV-10/1P-F/13 264918 Y7-264918 EATON ELECTRIC Phase busbar, 1-phase, 10qmm, angled gray, pin, 13SU

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-10/1P-F/13



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-10/1P-F/13
Catalog number	Y7-264918
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-F616D9DCB4
Generated	2026-08-03

Product Overview

Phase busbar, 1-phase, 10qmm, angled gray, pin, 13SU

Z-SV-10/1P-F/13

Eaton Distribution parts. Phase busbar, 1-phase, 10qmm, angled gray, pin, 13SU

Block busbar for PLN. (1 space units), Z-SI, supplied with end caps

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 264918 Model Code Z-SV-10/1P-F/13 EAN 4015082649180

Product Length/Depth 17.6 mm Product Height 15.3 mm Product Width 232 mm Product Weight 0.036 kg Compliances

RoHS conform Product specifications

Features Insulated

Can be cut to size Electric connection type Pin Rated surge voltage 0 KV Rated uninterrupted current (Iu) 50 A Suitable for number of devices 7 Number of poles Single-pole Color Other Rated short-time withstand current (Icw) 0 kA Cross section 10 mm² Number of modular spacings 1 Number of phases 1 Pitch dimensions 17.95 mm Rated operational voltage (Ue) - max 415 V Rated conditional short-circuit current (Iq) 25 kA Suitable for 13 devices

Devices with N-busbar

ETIM for 264918 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

1

Number of poles (EF001391)

1

Suitable for number of devices (EF007241)

7

Module width (EF007504)

17.95 mm

Cross section (EF000649)

10 mm²

Length (EF001438)

17.6 mm

Can be cut to size (EF015250)

Yes

Width in number of modular spacings (EF002950)

1

Rated permanent current I_u (EF001389)

50 A

Type of electric connection (EF003961)

Pin

Insulated (EF000019)

Yes

Rated surge voltage (EF002993)

0 kV

Conditioned rated short-circuit current I_q (EF001444)

25 kA

Max. rated operation voltage U_e (EF007357)

415 V

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Suitable for devices with N-conductor (EF007218)

Yes....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-10/1P-F/13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.