


INDUSTRIAL COMPONENT DATA

Z-SV-10/2P-2TE/13 264922 Y7-264922 EATON ELECTRIC

Phase busbar, 2-phases, 10qmm, pin, 13SU

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SV-10/2P-2TE/13



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SV-10/2P-2TE/13
Catalog number	Y7-264922
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-FF2A146590
Generated	2026-08-04

Product Overview

Phase busbar, 2-phases, 10qmm, pin, 13SU

Z-SV-10/2P-2TE/13

Block busbar for PLN. (1 space units), Z-SI, supplied with end caps

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Phase busbar, 2-phases, 10qmm, pin, 13SUBlock busbar for PLN. (1 space units), Z-SI, supplied with end capsTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar ( [ACN992011])Number of phases2Number of poles2Suitable for number of devices6Pitch dimensions17.95 mmCross section10 mm²Length232 mmNumber of modular spacings2Rated permanent current I_u50 AType of electric connectionPinInsulatedYesRated surge voltage0 kVConditioned rated short-circuit current I_q25 kA Max. rated operation voltage U_e415 VRated short-time withstand current I_{cw}0 kASuitable for devices with N-busbarYesSuitable for devices with auxiliary switchNo

ETIM for 264922 Low-voltage industrial controls and switchgear (EC000215)

Feature Name

Feature Value

Number of phases (EF000351)

2
Number of poles (EF001391)
2
Suitable for number of devices (EF007241)
0
Module width (EF007504)
17.95 mm
Cross section (EF000649)
10 mm²
Length (EF001438)
29.5 mm
Can be cut to size (EF015250)
Yes
Width in number of modular spacings (EF002950)
2
Rated permanent current I_u (EF001389)
50 A
Type of electric connection (EF003961)
Pin
Insulated (EF000019)
Yes
Rated surge voltage (EF002993)
0 kV
Conditioned rated short-circuit current I_q (EF001444)
25 kA
Max. rated operation voltage U_e (EF007357)
415 V
Rated short-time withstand....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SV-10/2P-2TE/13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.