

INDUSTRIAL COMPONENT DATA

FRBDM-B10/2/001-G/A 168294 Y7-168294 EATON ELECTRIC RCD/MCB comb. switch, 10A, 10mA, miniature circuit-break..

Brand: EATON - MOELLER | Manufacturer Part Number: FRBDM-B10/2/001-G/A



Manufacturer	EATON - MOELLER
MPN / Reference	FRBDM-B10/2/001-G/A
Catalog number	Y7-168294
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-F7078CF351
Generated	2026-08-05

Product Overview

RCD/MCB comb. switch, 10A, 10mA, miniature circuit-breaker type B trip characteristic, 2p, residual current circuit-breaker trip characteristic: A
FRBDM-B10/2/001-G/A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

RCD/MCB comb. switch, 10A, 10mA, miniature circuit-breaker type B trip characteristic, 2p, residual current circuit-breaker trip characteristic: A High-quality residual current circuit-breaker/miniature circuit-breaker with overcurrent protection independent of mains voltage; contact position display red-green; terminal rear plug protection; tri-stable slide catch-enables removal from an existing closure assembly; comprehensive accessory product range can be retrofitted; wide range of rated fault currents; rated operational currents up to 40 A; trip types B,C,D; rated switching capacity 10 kA; suitable for use in the free (on-site power and outdoor distribution board) to -25 °C; suitable for use in the free (on-site power and outdoor distribution board) to -25 °C Delivery program

Basic function Combined RCD/MCB devices Number of poles 2 pole Tripping characteristic B Application Switchgear for industrial and advanced commercial applications Rated current [I_n] 10 A Rated switching capacity according to IEC/EN 61009 10 kA Rated fault current [I_{Δn}] 0.01 A Type Type G/A (ÖVE E 8601) Tripping Short time-delayed s... Product range FRBdM Sensitivity Pulse-current sensitive Impulse withstand current Surge-proof, 3 kA Contact sequence Technical data Electrical Protected pole 2 Rated voltage according to IEC/EN 60947-2 [U_n] 240 V AC Rated frequency [f] 50 Hz Rated fault current [I_{Δn}] 10 mA Sensitivity Pulse-current sensitive Rated current [I_n] 10 A Tripping characteristic B Design verif...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBDM-B10/2/001-G/A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.