

INDUSTRIAL COMPONENT DATA

FRBM4-C32/3N/03 170953 Y7-170953 EATON ELECTRIC RCD/MCB combination switch, 32A, 300mA, miniature circuit-br..

Brand: EATON - MOELLER | Manufacturer Part Number: FRBM4-C32/3N/03



Manufacturer	EATON - MOELLER
MPN / Reference	FRBM4-C32/3N/03
Catalog number	Y7-170953
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-DE5D57533C
Generated	2026-08-03

Product Overview

RCD/MCB combination switch, 32A, 300mA, miniature circuit-br. type C trip characteristic, 3-ph+N, residual current circuit-br. trip characteristic: AC

FRBM4-C32/3N/03

Eaton Moeller series xEffect - FRBm4 RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 32A, 300mA, MCB trip type C, 3-ph+N, RCCB trip type: AC

High-quality residual current device/minature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary and Differential
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRBm4 RCBO - residual-current circuit breaker with overcurrent protection

Catalog Number 170953 Model Code FRBM4-C32/3N/03 EAN 4015081670819 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 70 mm Product Weight 0.461 kg Compliances CE Marked

RoHS conform Certifications CE

EN45545-2

IEC 61373 Delivery programme

Application Switchgear for industrial and advanced commercial applications Product range FRBm4 Basic function

Combined RCD/MCB devices Number of poles Three-pole + N Number of poles (protected) 4 Number of poles (total) 4

Tripping characteristic C Release characteristic C Rated current 32 A Fault current rating 0.3 A Sensitivity type AC current

sensitive Type RCBO Technical data - electrical

Voltage type AC Voltage rating 415 V - 415 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 500

V Rated impulse withstand voltage (Uimp) 4 kV Rated fault currents of product range 30, 100, 300 MilliAmpere Impulse

withstand current Partly surge-proof, 250 A Frequency rating 50 Hz Leakage current type AC Rated switching capacity 4.5

kA Rated switching capacity (IEC/EN 61009) 4.5 kA Rated short-circuit breaking capacity (EN 60947-2) 0 kA Rated

short-circuit breaking capacity (EN 61009) 4.5 kA Rated short-circuit breaking capacity (EN 61009-1) 4.5 kA Rated

short-circuit breaking capacity (IEC 60947-2) 0 kA Surge current capacity 0.25 kA Disconnection characteristic Undelayed

Trip...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBM4-C32/3N/03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.