

INDUSTRIAL COMPONENT DATA

FRBM6-B20/1N/003-A 177742 Y7-177742 EATON ELECTRIC RCD/MCB combination switch, 20A, 30mA, miniature circuit-..

Brand: EATON - MOELLER | Manufacturer Part Number: FRBM6-B20/1N/003-A



Manufacturer	EATON - MOELLER
MPN / Reference	FRBM6-B20/1N/003-A
Catalog number	Y7-177742
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-9F0E651526
Generated	2026-08-03

Product Overview

RCD/MCB combination switch, 20A, 30mA, miniature circuit-breaker type B trip characteristic, 1pole+N, residual current circuit-breaker trip characteristic: A

FRBM6-B20/1N/003-A

RCD/MCB combination, 20 A, 30 mA, MCB trip characteristic: B, 1p+N, RCD trip characteristic: A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary and Differential
--------------	--

Additional Product Information

RCD/MCB combination, 20 A, 30 mA, MCB trip characteristic: B, 1p+N, RCD trip characteristic: A High-quality residual current device/miniature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 20 A Equipment heat dissipation, current-dependent [Pvid] 5.4 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +40 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and

parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effectsMeets
th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBM6-B20/1N/003-A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.