

INDUSTRIAL COMPONENT DATA

FRBM6-C16/1N/003-G/A 177854 Y7-177854 EATON ELECTRIC RCD/MCB combination switch, 16A, 30mA, miniature circuit breaker

Brand: EATON - MOELLER | Manufacturer Part Number: FRBM6-C16/1N/003-G/A



Manufacturer	EATON - MOELLER
MPN / Reference	FRBM6-C16/1N/003-G/A
Catalog number	Y7-177854
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-C30708D734
Generated	2026-08-06

Product Overview

RCD/MCB combination switch, 16A, 30mA, miniature circuit-breaker type C trip characteristic, 1pole+N, residual current circuit-breaker trip characteristic: G/A

FRBM6-C16/1N/003-G/A

Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB combination, 16A, 30mA, MCB C trip char., 1pole+N, RCCB trip char.: G/A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection
Catalog Number 177854 Model Code FRBM6-C16/1N/003-G/A EAN 4015081724277 Product Length/Depth 80 mm
Product Height 75 mm Product Width 35 mm Product Weight 0.216 kg Compliances CE Marked
RoHS conform Certifications CE Delivery programme
Application Switchgear for industrial and advanced commercial applications Basic function Combined RCD/MCB devices
Number of poles Single-pole + N Number of poles (protected) 1 Number of poles (total) 2 Release characteristic C
Amperage Rating 16 A Rated current 16 A Fault current rating 0.03 A Type RCBO Technical data - electrical
Voltage type AC Voltage rating 240 V - 240 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 500 V
Rated impulse withstand voltage (Uimp) 4 kV Frequency rating 50 Hz Leakage current type A Rated short-circuit breaking capacity (EN 60947-2) 0 kA Rated short-circuit breaking capacity (EN 61009) 6 kA Rated short-circuit breaking capacity (EN

61009-1) 6 kA Rated short-circuit breaking capacity (IEC 60947-2) 0 kA Surge current capacity 3 kA Disconnection characteristic Short-time delayed Overvoltage category III Pollution degree 2 Technical data - mechanical Width in number of modular spacings 2 Built-in depth 75.5 mm Degree of protection IP20 Connectable conductor cross section (solid-core) - min 1 mm² Connectable conductor cross section (solid-core) - ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBM6-C16/1N/003-G/A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.