

INDUSTRIAL COMPONENT DATA

**FRBMM-B25/2/003 170876 Y7-170876 EATON ELECTRIC
RCD/MCB combination switch, 25A, 30mA, miniature
circuit-br...**

Brand: EATON - MOELLER | Manufacturer Part Number: FRBMM-B25/2/003



Manufacturer	EATON - MOELLER
MPN / Reference	FRBMM-B25/2/003
Catalog number	Y7-170876
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-323B2D43DA
Generated	2026-08-04

Product Overview

RCD/MCB combination switch, 25A, 30mA, miniature circuit-br. type B trip characteristic, 2p, residual current circuit-br. trip characteristic: AC

FRBMM-B25/2/003

Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 25A, 30mA, MCB trip type B, 2p, RCCB trip type: AC

High-quality residual current device/miniature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary and Differential
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection

Catalog Number 170876 Model Code FRBMM-B25/2/003 EAN 4015081674343 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 35 mm Product Weight 0.25 kg Compliances CE Marked

RoHS conform Certifications CE

EN45545-2

IEC 61373 Delivery programme

Application Switchgear for industrial and advanced commercial applications Product range FRBmM Basic function

Combined RCD/MCB devices Number of poles Two-pole Number of poles (protected) 2 Number of poles (total) 2 Release characteristic B Amperage Rating 25 A Rated current 25 A Fault current rating 0.03 A Sensitivity type AC current sensitive

Type RCBO Technical data - electrical

Voltage type AC Voltage rating 240 V - 240 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 500 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault currents of product range 10, 30, 100, 300 MilliAmpere Impulse

withstand current Partly surge-proof, 250 A Frequency rating 50 Hz Leakage current type AC Rated switching capacity 10

kA Rated switching capacity (IEC/EN 61009) 10 kA Rated short-circuit breaking capacity (EN 60947-2) 0 kA Rated

short-circuit breaking capacity (EN 61009) 10 kA Rated short-circuit breaking capacity (EN 61009-1) 10 kA Rated

short-circuit breaking capacity (IEC 60947-2) 0 kA Surge current capacity 0.25 kA Disconnection characteristic Undelayed

Tripping Non-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBMM-B25/2/003 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.