

INDUSTRIAL COMPONENT DATA

FRBMM-C13/2/01-A 170821 Y7-170821 EATON ELECTRIC

Auxiliary contact, 1N/O+3N/C, surface mounting, screw

conne..

Brand: EATON - MOELLER | Manufacturer Part Number: FRBMM-C13/2/01-A



Manufacturer	EATON - MOELLER
MPN / Reference	FRBMM-C13/2/01-A
Catalog number	Y7-170821
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-E46AC04435
Generated	2026-08-04

Product Overview

Auxiliary contact, 1N/O+3N/C, surface mounting, screw connection

FRBMM-C13/2/01-A

Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 13A, 100mA, MCB trip type C, 2p, RCCB trip type: A, G

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection
Catalog Number 170821 Model Code FRBMM-C13/2/01-A EAN 4015081673889 Product Length/Depth 80 mm Product
Height 75.5 mm Product Width 35 mm Product Weight 0.25 kg Compliances RoHS conform Certifications CE
EN45545-2

IEC 61373 Delivery programme

Application Switchgear for industrial and advanced commercial applications Product range FRBmM Basic function

Combined RCD/MCB devices Number of poles Two-pole Number of poles (protected) 2 Number of poles (total) 2 Release
characteristic C Amperage Rating 13 A Rated current 13 A Fault current rating 0.1 A Sensitivity type Pulse-current sensitive
Type RCBO Technical data - electrical

Voltage type AC Voltage rating 240 V - 240 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 500 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault currents of product range 10, 30, 100, 300 MilliAmpere Impulse withstand current Partly surge-proof, 250 A Frequency rating 50 Hz Leakage current type A Rated switching capacity 10 kA Rated switching capacity (IEC/EN 61009) 10 kA Rated short-circuit breaking capacity (EN 60947-2) 0 kA Rated short-circuit breaking capacity (EN 61009) 10 kA Rated short-circuit breaking capacity (EN 61009-1) 10 kA Rated short-circuit breaking capacity (IEC 60947-2) 0 kA Surge current capacity 0.25 kA Disconnection characteristic Undelayed Tripping Non-delayed....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBMM-C13/2/01-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.