

INDUSTRIAL COMPONENT DATA

**FRBMM-D16/1N/01 170542 Y7-170542 EATON ELECTRIC
combination switch, 16A, 100mA, D curve , 1P+N, class AC**

Brand: EATON - MOELLER | Manufacturer Part Number: FRBMM-D16/1N/01



Manufacturer	EATON - MOELLER
MPN / Reference	FRBMM-D16/1N/01
Catalog number	Y7-170542
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-222758D32D
Generated	2026-08-05

Product Overview

combination switch, 16A, 100mA, D curve , 1P+N, class AC

FRBMM-D16/1N/01

Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 16A, 100mA, MCB trip type D, 1-ph+N, RCCB trip type: AC

High-quality residual current device/miniature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection

Catalog Number 170542 Model Code FRBMM-D16/1N/01 EAN 4015081671403 Product Length/Depth 80 mm Product

Height 75 mm Product Width 35 mm Product Weight 0.187 kg Compliances CE Marked

RoHS conform Certifications CE

EN45545-2

IEC 61373 Delivery programme

Application Switchgear for industrial and advanced commercial applications Product range FRBmM Basic function Combined RCD/MCB devices Number of poles Single-pole + N Number of poles (protected) 1 Number of poles (total) 2 Release characteristic D Amperage Rating 16 A Rated current 16 A Fault current rating 0.1 A Sensitivity type AC current sensitive Type RCBO Technical data - electrical

Voltage type AC Voltage rating 240 V - 240 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 500 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault currents of product range 10, 30, 100, 300 MilliAmpere Impulse withstand current Partly surge-proof, 250 A Frequency rating 50 Hz Leakage current type AC Rated switching capacity 10 kA Rated switching capacity (IEC/EN 61009) 10 kA Rated short-circuit breaking capacity (EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 61009) 10 kA Rated short-circuit breaking capacity (EN 61009-1) 10 kA Rated short-circuit breaking capacity (IEC 60947-2) 15 kA Surge current capacity 0.25 kA Disconnection characteristic Undelayed Trippi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRBMM-D16/1N/01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.