

INDUSTRIAL COMPONENT DATA

FRCDM-63/4/003-G/BFQ 179532 Y7-179532 EATON ELECTRIC

Digital residual current circuit-breaker, 63A, 4p, 30mA..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCDM-63/4/003-G/BFQ



Manufacturer	EATON - MOELLER
MPN / Reference	FRCDM-63/4/003-G/BFQ
Catalog number	Y7-179532
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-91A6867CF2
Generated	2026-08-06

Product Overview

Digital residual current circuit-breaker, 63A, 4p, 30mA, type G/BFQ

FRCDM-63/4/003-G/BFQ

Eaton Moeller series xEffect - FRCdM Type B, B+, Bfq RCCB. Digital residual current circuit-breaker, all-current sensitive, 63 A, 4p, 30 mA, type G/BFQ

Residual current circuit-breaker FRCdM, 4 pole, Rated current In: 63 A, Rated short-circuit strength Icn: 10 with back-up fuse kA, Rated fault current I_N: 0.03 A, Residual current circuit-breaker - frequency converter-proof

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCdM Type B, B+, Bfq RCCB Catalog Number 179532 Model Code FRCDM-63/4/003-G/BFQ EAN 4015081746170 Product Length/Depth 80 mm Product Height 72.6 mm Product Width 70 mm Product Weight 0.368 kg Compliances RoHS conform Certifications IEC/EN 62423

IEC/EN 61008

EN45545-2

IEC 61373

ÖVE E 8601 Delivery program

Application Number of poles Four-pole Tripping time Short time-delayed

10 ms delayed Amperage Rating 63 A Rated short-circuit strength 10 kA Fault current rating 30 mA Sensitivity type All

current sensitive - frequency converter-proof Impulse withstand current 3 kA (8/20 us) surge-proof Type Current test marks as per inscription

Dry auxiliary contact: > 100,000 electrical switching operations per minute at 2 A 30 VDC resistive load

Dry auxiliary contact: > 5 x 100,000 electrical switching operations per minute at 1 A 30 VDC resistive load

Maximum operating temperature is 60 °C in accordance with the de-rating table

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Voltage rating - min 50 VAC Voltage rating - max 456 VAC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.03 A Rated fault current - max 0.03 A Frequency rating 50 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type B Rated residual making and breaking capacity 630 A Admissible back-up fuse...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMD-63/4/003-G/BFQ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.