

INDUSTRIAL COMPONENT DATA

FRCDM-63/4/01-S/F EP-501271 Y7-501271 EATON ELECTRIC RCCB, 63A, 4p, 100mA, Type S/F

Brand: EATON - MOELLER | Manufacturer Part Number: FRCDM-63/4/01-S/F



Manufacturer	EATON - MOELLER
MPN / Reference	FRCDM-63/4/01-S/F
Catalog number	Y7-501271
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-2CDA46B489
Generated	2026-08-05

Product Overview

RCCB, 63A, 4p, 100mA, Type S/F

Eaton Moeller series xEffect - FRCDM Type B, B+, Bfq RCCB, 63A, 4p, 100mA, Type S/F

Residual current circuit-breaker FRCDM, 4 pole, Rated current In: 63 A, Rated short-circuit strength Icn: 10 with back-up fuse kA, Rated fault current I_N: 0.1 A, Type S/F; Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCDM Type AC, A, U, R RCCB Catalog Number EP-501271 Model Code

FRCDM-63/4/01-S/F EAN 9010653039082 Product Length/Depth 80 mm Product Height 80 mm Product Width 70 mm

Product Weight 0.32 kg Compliances RoHS conform Certifications CE Delivery program

Application xEffect - Switchgear for industrial and advanced commercial applications Number of poles Four-pole Tripping time 40 ms delayed, selective (type S) Amperage Rating 63 A Rated short-circuit strength 10 kA Fault current rating 0.1 A Type Residual current circuit-breakers, Digital, Type S/F Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Voltage rating - min 196 VAC Voltage rating - max 264 VAC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV

Rated fault current - min 100 mA Frequency rating 50 Hz Short-circuit rating 63 A (max. admissible back-up fuse) Leakage current type F Rated residual making and breaking capacity 630 A Admissible back-up fuse 63 A gG/gL Admissible back-up fuse overload - max 63 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 5 kA Pollution

degree 2 Lifespan, electrical 4000 operations Technical data - electrical - dry auxiliary contact

Rated switching capacity (resistive load) of auxiliary contact at 30 V DC 2 A Rated switching capacity (resistive load) of auxiliary contact at 240 V AC 0.25 A Switch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCDM-63/4/01-S/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.