

INDUSTRIAL COMPONENT DATA

FRCmM-100/4/003-A-400 304194 Y7-304194 EATON ELECTRIC Residual current circuit breaker (RCCB), 100 A, 4 p, 3..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCmM-100/4/003-A-400



Manufacturer	EATON - MOELLER
MPN / Reference	FRCmM-100/4/003-A-400
Catalog number	Y7-304194
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-2948882AF1
Generated	2026-08-05

Product Overview

Residual current circuit breaker (RCCB), 100 A, 4 p, 30 mA, type A, 400 V

Eaton Moeller series xEffect - FRCmM Type AC, A, U, R Residual current circuit breaker (RCCB), 100 A, 4 p, 30 mA, type A, 400 V

Mains voltage-independent residual current circuit-breaker for fault protection and additional protection, 100 A, 4 p, 30 mA, type A, 400 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type AC, A, U, R RCCB Catalog Number 304194 Model Code FRCmM-100/4/003-A-400 EAN 9010238196551 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.298 kg Compliances RoHS conform Certifications IEC/EN 61008 EN45545-2

IEC 61373 Delivery program

Application Number of poles Four-pole Tripping time Non-delayed Amperage Rating 100 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 30 mA Sensitivity type Pulse-current sensitive Impulse withstand current 250 A (8/20 us) surge-proof

Partly surge-proof 250 A Type FRCmM

Residual current circuit breakers

Type A

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.03 A Rated fault current - max 0.03 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 100 A (max. admissible back-up fuse) Leakage current type A Rated residual making and breaking capacity 1000 A Admissible back-up fuse overload - max 80 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 0.25 kA Test circuit range 356 V AC - 456 V AC Pollution degree 2 Lifespan, electrical 4000 operations Technical data - mechanical
Frame 45 mm Width in number of modular spacings 4 Built-in width (number of units) 70 mm (4 SU) Built-in depth 70.5 mm Mounting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCmM-100/4/003-A-400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.