

INDUSTRIAL COMPONENT DATA

FRCMM-100/4/003-G/F 187412 Y7-187412 EATON ELECTRIC
Residual current circuit breaker (RCCB), 100A, 4p, 30mA,..

Brand: EATON - MOELLER | Manufacturer Part Number: FRCMM-100/4/003-G/F



Manufacturer	EATON - MOELLER
MPN / Reference	FRCMM-100/4/003-G/F
Catalog number	Y7-187412
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-5CD7C87128
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 100A, 4p, 30mA, type G/F

FRCMM-100/4/003-G/F

Eaton Moeller series xEffect - FRCmM Type F RCCB. Residual current circuit breaker (RCCB), 100A, 4p, 30mA, type G/F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FRCmM Type F RCCB Catalog Number 187412 Model Code FRCMM-100/4/003-G/F EAN 4015081824700 Product Length/Depth 80 mm Product Height 76 mm Product Width 70 mm Product Weight 0.386 kg Compliances RoHS conform Certifications IEC/EN 62423

EN45545-2

IEC 61373

IEC/EN 61008 Delivery program

Application Number of poles Four-pole Tripping time 10 ms delayed Amperage Rating 100 A Rated short-circuit strength 10 kA with back-up fuse Fault current rating 30 mA Sensitivity type Pulse-current sensitive Impulse withstand current 3 kA (8/20 us) surge-proof Type FRCmM

Residual current circuit breakers

Type G/F (ÖVE E 8601)

Technical data - electrical

Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V AC Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Rated fault current - min 0.03 A Rated fault current - max 0.03 A Frequency rating 50 Hz / 60 Hz Short-circuit rating 100 A (max. admissible back-up fuse) Leakage current type Other Rated residual making and breaking capacity 1000 A Admissible back-up fuse overload - max 80 A gG/gL Rated short-time withstand current (Icw) 10 kA Surge current capacity 3 kA Test circuit range 184 V AC - 440 V AC Pollution degree 2 Radiation resistance Frequency mix (10 Hz, 50 Hz, 1000 Hz) enhanced sensitivity Lifespan, electrical 4000 operations Technical data - mechanical Frame 45 mm Width in number of modular spacings 4 Built...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FRCMM-100/4/003-G/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.